




Aluminium Alloy Rectangular Tube 6061 & 6082 T6

Temper: H116 | H321 | H111 | H112

Certified to: ASTM B928 (G66/G67 Tested) with ABS, BV, DNV
and LR Cert.



Thickness	Width	Width	Length	Kgs / Mtr
1.57mm	25.4mm	38.1mm	6000mm	0.515
2.0mm	20.0mm	40.0mm	6000mm	0.606
3.0mm	25.4mm	50.8mm	6000mm	0.783
	19.05mm	38.1mm	6000mm	0.831
	25.4mm	101.6mm	6000mm	1.966
	25.4mm	38.1mm	6000mm	0.906
	25.4mm	50.8mm	6000mm	1.141
	25.4mm	63.5mm	6000mm	1.348
	25.4mm	76.2mm	6000mm	1.458
	38.1mm	101.6mm	6000mm	2.173
	38.1mm	50.80mm	6000mm	1.348
	38.1mm	76.20mm	6000mm	1.761
	50.8mm	101.6mm	6000mm	2.383
	50.8mm	127.0mm	6000mm	2.796
	50.8mm	152.4mm	6000mm	3.208
	50.8mm	203.2mm	6000mm	4.036
	50.8mm	76.20mm	6000mm	1.968
	76.2mm	101.6mm	6000mm	2.796
	76.2mm	127.0mm	6000mm	3.209
	76.2mm	152.4mm	6000mm	3.621
4.0mm	40.0mm	60.00mm	6000mm	1.995
4.5mm	25.4mm	50.8mm	6000mm	1.64
	38.1mm	76.2mm	6000mm	2.571
	50.8mm	101.6mm	6000mm	3.498

Thickness	Width	Width	Length	Kgs / Mtr
	50.8mm	76.2mm	6000mm	2.88
5.0mm	100.0mm	200.0mm	6000mm	7.867
6.0mm	50.8mm	101.6mm	6000mm	4.57
	50.8mm	76.2mm	6000mm	3.743
6.35mm	76.2mm	101.6mm	6000mm	5.686

Custom & Indent Items:

Dimensions not listed above and items marked Indent are available via mill / works production on a made-to-order basis. Subject to minimum order quantities (MOQ).