




Aluminium Alloy Rod 6061 & 6082 T6 & T6511



Temper: H116 | H321 | H111 | H112

Certified to: ASTM B928 (G66/G67 Tested) with ABS, BV, DNV
and LR Cert.

Diameter	Length	Kgs / Mtr
6.35mm	6000mm	0.084
8.00mm	6000mm	0.135
10.00mm	6000mm	0.213
12.70mm	6000mm	0.345
15.88mm	6000mm	0.537
19.05mm	6000mm	0.773
22.23mm	6000mm	1.054
25.40mm	6000mm	1.375
31.75mm	4880mm	2.148
38.10mm	4880mm	3.093
44.45mm	4880mm	4.209
50.80mm	4880mm	5.498
57.15mm	4880mm	6.959
63.50mm	2440mm	8.59
69.85mm	2440mm	10.389
76.20mm	2440mm	12.373
82.55mm	2440mm	14.516
88.90mm	2440mm	16.84
95.25mm	2440mm	19.455
101.60mm	2440mm	21.996
107.95mm	2440mm	24.828
114.30mm	2440mm	27.836
120.65mm	2440mm	31.015
127.00mm	2440mm	34.713

Diameter	Length	Kgs / Mtr
133.35mm	2440mm	38.209
139.70mm	2440mm	41.64
146.05mm	2440mm	46.053
152.4mm	2440mm	49.61
165.1mm	2440mm	58.5
177.8mm	2440mm	67.903
190.5mm	2440mm	77.22
203.2mm	2440mm	88.744
215.9mm	2440mm	100.18
228.6mm	2440mm	111.107
241.3mm	2440mm	124.37
254.0mm	2440mm	137.52
266.7mm	2440mm	151.84
279.4mm	2440mm	167.98
292.1mm	2440mm	183.948
304.8mm	2440mm	198.608
330.2mm	2440mm	232.93
355.6mm	2440mm	270.5
381.0mm	2440mm	310.11
406.4mm	1200mm	352.84
431.8mm	1000mm	398.32
457.2mm	1000mm	446.56
500.0mm	1000mm	534.08

Custom & Indent Items:

Dimensions not listed above and items marked Indent are available via mill / works production on a made-to-order basis. Subject to minimum order quantities (MOQ).