




# Aluminium Alloy Square Bar 6061 & 6082 T6511

Temper: H116 | H321 | H111 | H112

Certified to: ASTM B928 (G66/G67 Tested) with ABS, BV, DNV and LR Cert.



| Thickness | Length | Kgs / Mtr |
|-----------|--------|-----------|
| 6.35mm    | 6000mm | 0.109     |
| 8.00mm    | 6000mm | 0.172     |
| 9.53mm    | 6000mm | 0.246     |
| 10.00mm   | 6000mm | 0.27      |
| 12.70mm   | 6000mm | 0.437     |
| 15.88mm   | 6000mm | 0.685     |
| 19.05mm   | 6000mm | 0.984     |
| 22.23mm   | 6000mm | 1.34      |
| 25.40mm   | 6000mm | 1.75      |
| 31.75mm   | 4880mm | 2.734     |
| 38.10mm   | 4880mm | 3.939     |
| 44.45mm   | 4880mm | 5.36      |
| 50.80mm   | 4880mm | 7         |
| 57.15mm   | 2440mm | 8.861     |
| 63.50mm   | 2440mm | 10.939    |
| 70.00mm   | 2440mm | 13.291    |
| 76.20mm   | 2440mm | 15.75     |
| 88.90mm   | 2440mm | 21.443    |
| 101.6mm   | 2440mm | 28.168    |
| 114.3mm   | 2440mm | 35.381    |
| 127.0mm   | 2440mm | 44.079    |
| 130.0mm   | 2440mm | 53.416    |

---

### **Custom & Indent Items:**

Dimensions not listed above and items marked Indent are available via mill / works production on a made-to-order basis. Subject to minimum order quantities (MOQ).