




Aluminium Alloy T Bar 6061 & 6082 T6

Temper: H116 | H321 | H111 | H112

Certified to: ASTM B928 (G66/G67 Tested) with ABS, BV, DNV
and LR Cert.



Thickness1	Width	Thickness2	Height	Length	Kgs / Mtr
3.0mm	25.4mm	3.0mm	25.4mm	6000mm	0.376
	31.75mm	3.0mm	31.75mm	6000mm	0.46
	38.1mm	3.0mm	38.1mm	6000mm	0.595
4.0mm	50.8mm	3.0mm	50.8mm	6000mm	0.811
	40.0mm	4.0mm	40.0mm	6000mm	0.841
	38.1mm	4.5mm	38.1mm	6000mm	0.903
4.5mm	50.8mm	4.5mm	50.8mm	6000mm	1.213
	38.1mm	4.76mm	76.2mm	6000mm	1.443
	50.0mm	5.0mm	100mm	6000mm	1.995
4.76mm	50.0mm	3.5mm	150mm	6000mm	2.083
	50.8mm	5.0mm	50.8mm	6000mm	1.338
	100mm	6.0mm	125.0mm	6000mm	3.593
5.0mm	38.1mm	6.0mm	38.1mm	4880mm	1.141
	40.0mm	6.0mm	80.0mm	6000mm	1.883
	50.0mm	4.0mm	125.0mm	6000mm	2.131
6.0mm	50.0mm	4.0mm	60.0mm	6000mm	1.416
	50.8mm	6.0mm	101.6mm	6000mm	2.411
	50.8mm	6.0mm	50.8mm	6000mm	1.583
6.0mm	50.8mm	6.0mm	63.5mm	6000mm	1.791
	50.8mm	6.0mm	76.2mm	6000mm	1.998
	63.5mm	6.0mm	63.50mm	6000mm	2.011
6.0mm	65.0mm	6.0mm	100.0mm	6000mm	2.616
	76.2mm	6.0mm	76.20mm	6000mm	2.41
	80.0mm	6.0mm	156.0mm	6000mm	3.777

Thickness1	Width	Thickness2	Height	Length	Kgs / Mtr
8.0mm	45.0mm	5.0mm	100mm	6000mm	2.241
	75.0mm	6.0mm	125mm	6000mm	3.558
10.0mm	50.0mm	6.0mm	200mm	6000mm	4.476

Custom & Indent Items:

Dimensions not listed above and items marked Indent are available via mill / works production on a made-to-order basis. Subject to minimum order quantities (MOQ).