




Aluminium Alloy U Channel 6061 & 6082 T6

Temper: H116 | H321 | H111 | H112

Certified to: ASTM B928 (G66/G67 Tested) with ABS, BV, DNV and LR Cert.



Thickness1	Height	Thickness2	Width	Length	Kgs / Mtr
2.4mm	19.05mm	2.4mm	19.05mm	6000mm	0.34
	25.40mm	2.4mm	25.40mm	6000mm	0.463
3.0mm	25.40mm	3.0mm	25.40mm	6000mm	0.571
	31.75mm	3.0mm	31.75mm	6000mm	0.703
	38.10mm	3.0mm	38.10mm	6000mm	0.853
	50.80mm	3.0mm	50.80mm	6000mm	1.19
	19.05mm	3.0mm	38.10mm	6000mm	0.553
	25.40mm	3.0mm	50.80mm	6000mm	0.778
	25.40mm	3.0mm	76.20mm	6000mm	0.983
	25.40mm	3.0mm	101.60mm	6000mm	1.153
	38.10mm	3.0mm	76.20mm	6000mm	1.186
	50.80mm	3.0mm	101.60mm	6000mm	1.603
6.0mm	25.40mm	6.0mm	50.80mm	6000mm	1.458
	25.40mm	6.0mm	76.20mm	6000mm	1.871
	25.40mm	6.0mm	101.60mm	6000mm	2.285
	38.10mm	6.0mm	76.20mm	6000mm	2.25
	50.80mm	6.0mm	76.20mm	6000mm	2.698
	50.80mm	6.0mm	101.60mm	6000mm	3.108
	50.80mm	6.0mm	127.00mm	6000mm	3.525
	50.80mm	6.0mm	152.40mm	6000mm	3.938
8.0mm	76.20mm	6.0mm	152.40mm	6000mm	5.556
9.53mm	50.80mm	9.53mm	152.40mm	6000mm	5.911
	76.20mm	9.53mm	127.00mm	6000mm	6.803
	76.20mm	6.35mm	152.40mm	6000mm	6.25

Thickness1	Height	Thickness2	Width	Length	Kgs / Mtr
12.7mm	76.20mm	9.53mm	152.40mm	3660mm	8.412
	76.20mm	9.53mm	177.80mm	3660mm	8.948
	76.20mm	9.53mm	203.20mm	4880mm	9.655
	76.20mm	9.53mm	228.60mm	6000mm	10.64
13.92mm	101.6mm	9.35mm	203.20mm	4200mm	12.311

Custom & Indent Items:

Dimensions not listed above and items marked Indent are available via mill / works production on a made-to-order basis. Subject to minimum order quantities (MOQ).