



Aluminum Alloy Sheet & Plate 5383

Temper: H116 | H321

Certified to ASTM B928 (G66/G67 Tested) with ABS, BV, DNV and LR Cert.



Thickness	Width	Length
3.0 mm	1220 mm	2440 mm
	1500 mm	6000 mm
	2000 mm	6000 mm
	2200 mm	9000 mm
4.0 mm	1220 mm	2440 mm
	1500 mm	6000 mm
	2000 mm	6000 mm
	2200 mm	9000 mm
4.5 mm	1220 mm	2440 mm
	1500 mm	6000 mm
	2000 mm	6000 mm
	2200 mm	9000 mm
5.0 mm	1220 mm	2440 mm
	1500mm	6000 mm
	2000 mm	6000 mm
	2200 mm	9000 mm
6.0 mm	1220 mm	2440 mm
	1500mm	6000 mm
	2000 mm	6000 mm
	2200 mm	9000 mm
7.0 mm	1220 mm	2440 mm
	1500mm	6000 mm
	2000 mm	6000 mm
	2200 mm	9000 mm
8.0 mm	1220 mm	2440 mm

Thickness	Width	Length
	1500mm	6000 mm
	2000 mm	6000 mm
	2200 mm	9000 mm
10.0 mm	1220 mm	2440 mm
	1500mm	6000 mm
	2000 mm	6000 mm
	2200 mm	9000 mm
12.0 mm	1220 mm	2440 mm
	1500mm	6000 mm
	2000 mm	6000 mm
	2200 mm	9000 mm
15.0 mm	1220 mm	2440 mm
	1500mm	6000 mm
	2000 mm	6000 mm
	2200 mm	9000 mm
16.0 mm	1220 mm	2440 mm
	1500mm	6000 mm
	2000 mm	6000 mm
	2200 mm	9000 mm
20.0 mm	1220 mm	2440 mm
	1500mm	6000 mm
	2000 mm	6000 mm
	2200 mm	9000 mm
25.0 mm	1220 mm	2440 mm
	1500mm	6000 mm

Thickness	Width	Length
30.0 mm	2000 mm	6000 mm
	2200 mm	9000 mm
	1220 mm	2440 mm
	1500mm	6000 mm
32.0 mm	2000 mm	6000 mm
	2200 mm	9000 mm
	1220 mm	2440 mm
	1500mm	6000 mm
35.0 mm	2000 mm	6000 mm
	2200 mm	9000 mm
	1220 mm	2440 mm
	1500mm	6000 mm
38.0 mm	2000 mm	6000 mm
	2200 mm	9000 mm
	1220 mm	2440 mm
	1500mm	6000 mm
40.0 mm	2000 mm	6000 mm
	2200 mm	9000 mm
	1220 mm	2440 mm
	1500 mm	6000 mm
50.0 mm	2000 mm	6000 mm
	2200 mm	9000 mm
	1220 mm	2440 mm
	1500 mm	6000 mm
	2000 mm	6000 mm
	2200 mm	9000 mm
	1220 mm	2440 mm
	1500 mm	6000 mm

Custom & Indent Items:

Dimensions not listed above and items marked Indent are available via mill / works production on a made-to-order basis. Subject to minimum order quantities (MOQ).